

BEACH FLAG MATERIAL

Code	KW 029 - PES – AIR MESH FABRIC
Weight	115g/m2 +-(5gr)
Standart Sizes	105cm, 160cm ,205cm ,260cm, 320cm x 100mt
Printable Ink	Direct Dye Sub, Latex, Uv-Curable
Application	Beach Flags / Flags / Facade covering
Material	100 % Polyester
Max. Heat Shrinkage	200 °C / 110 seconds; Lengthwise -%1.1 / Crosswise -%0.8
Tensile Strength	30/35 warp/weft (daN) DIN EN ISO 13934-1
Tear Resistance	14/13 warp/weft (N) DIN EN ISO 13937-4
Finishing	Digital Coating
Packaging	7,65cm paper core, wrapped with stretch film + put in a cardboard box

Our product enables to have vivid colors and good printing quality with SUB., LATEX & UV inks.

(Test printing is suggested before the printing job.)



Ink Type



Sub Direct and Paper Transfer



UV Printable



Latex Printable



Fire Retardant



Fire Retardant



Fire Retardant



European Standard



Cutting



Cold Cut

*Optional



Be Green ♻️



All above released specifications and informations are for guidance purposes only. Our policy of continuous improvement may result in changes , we therefore reserve the right to alter the specifications and the informations at anytime without notice.