

ECO FLAG MATERIAL

Code	KW 045 - PES – GLOSSY KNITTED SATIN
Weight	90g/m2 +-(5gr)
Standart Sizes	105cm, 160cm ,205cm ,260cm, 320cm x 100mt
Printable Ink	Direct Dye Sub, Latex, Uv-Curable
Application	Short term flags / Beach Flags
Material	100 % Polyester
Max. Heat Shrinkage	200 °C / 110 seconds; Lengthwise -%2.0 / Crosswise -%1.2
Tensile Strength	27/110 warp/weft (daN) DIN EN ISO 13934-1
Tear Resistance	23/41 warp/weft (N) DIN EN ISO 13937-4
Finishing	Digital Coating
Packaging	7,65cm paper core, wrapped with stretch film + put in a cardboard box

Our product enables to have vivid colors and good printing quality with SUB., LATEX & UV inks.

(Test printing is suggested before the printing job.)



Ink Type

SUB

Sub Direct and Paper Transfer

UV

UV Printable

LTX

Latex Printable



Fire Retardant

B1

Fire Retardant

M1

Fire Retardant

EN 13501

European Standard



Cutting

COLD

Cold Cut

*Optional



Be Green



All above released specifications and informations are for guidance purposes only. Our policy of continuous improvement may result in changes , we therefore reserve the right to alter the specifications and the informations at anytime without notice.